

UNIVERSITY OF
Southampton


Conditional Requests

COMP3220 Web Infrastructure

Dr Nicholas Gibbins – nmg@ecs.soton.ac.uk

The Lost Update problem

If two or more clients are modifying a resource at the same time, how do we avoid *lost updates*?



Conditional requests

Some HTTP methods are *unsafe*; they alter the state of resources

Lost updates occur only when carrying out unsafe methods

- Avoid by checking to see whether the state of a resource (i.e. its representation) has changed between the GET and the PUT

Can also be used to avoid unnecessary safe methods

Comparison of representations in terms of validators that describe resource versions

- Strong validation: checks whether representations are byte-for-byte identical
- Weak validation: checks whether representations contain “the same content”

Entity tags

Entity tags are identifiers for resource versions (can be weak or strong)

Supplied by the server using the ETag: header:

- ETag: "38be-5af769c088685" - a strong entity tag
- ETag: w/"0023" - a weak entity tag (denoted by the "W/")
- ETag: * - an entity tag matching any resource

If-Match: *<etag>*, *<etag>*, ...

- Only carry out the operation if the resource entity tag matches one of those listed
- If no matches, return 412 Precondition Failed

If-None-Match: *<etag>*, *<etag>*, ...


- Only carry out the operation if the resource entity tag does not match any of those listed
- If matches, return 304 Not Modified for safe methods, or 412 Precondition Failed for unsafe methods



```
GET / HTTP/1.1  
Host: www.example.com
```

```
HTTP/1.1 200 OK  
Content-Type: text/html  
ETag: "39d5-5943f8fdc2607"
```


<representation>



```
PUT / HTTP/1.1  
Host: www.example.com  
If-Match: "39d5-5943f8fdc2607"
```

<new representation>

```
HTTP/1.1 200 OK  
Content-Type: text/html  
ETag: "47cf-b922e4f191138"
```






```
GET / HTTP/1.1  
Host: www.example.com
```

```
HTTP/1.1 200 OK  
Content-Type: text/html  
ETag: "39d5-5943f8fdc2607"
```

<representation>




http://www.example.com/ is modified – new ETag is 4b4f-77a6c3ab117a2



```
PUT / HTTP/1.1  
Host: www.example.com  
If-Match: "39d5-5943f8fdc2607"
```

<new representation>


```
HTTP/1.1 412 Precondition Failed  
Content-Type: text/html  
ETag: "4b4f-77a6c3ab117a2"
```





```
GET / HTTP/1.1  
Host: www.example.com  
If-None-Match: "4b4f-77a6c3ab117a2"
```

```
HTTP/1.1 304 Not Modified
```



Timestamps

Supplied by the server using the Last-Modified: header:

- Last-Modified: Fri, 18 Sep 2020 17:25:23 GMT

If-Modified-Since: *<dayname>*, *<day>* *<month>* *<year>* *<hour>*:*<min>*:*<sec>* GMT

- Only carry out the operation if the resource timestamp is after the given date
- Return 304 Not Modified if before the given date


If-Unmodified-Since: *<dayname>*, *<day>* *<month>* *<year>* *<hour>*:*<min>*:*<sec>* GMT

- Only carry out the operation if the resource timestamp is not after the given date
- Return 412 Precondition Failed if after the given date



```
GET / HTTP/1.1  
Host: www.example.com
```

```
HTTP/1.1 200 OK  
Content-Type: text/html  
Last-Modified: Mon, 14 Sep 2020 12:23:01 GMT  
  
<representation>
```




http://www.example.com/ is modified on Tue, 15 Sep 2020 14:34:07 GMT



```
PUT / HTTP/1.1  
Host: www.example.com  
If-Unmodified-Since: Mon, 14 Sep 2020 12:23:01 GMT  
  
<new representation>
```


```
HTTP/1.1 412 Precondition Failed  
Content-Type: text/html  
Last-Modified: Tue, 15 Sep 2020 14:34:07 GMT
```





```
GET / HTTP/1.1  
Host: www.example.com  
If-Modified-Since: Tue, 15 Sep 2020 14:34:07 GMT
```

```
HTTP/1.1 304 Not Modified
```



Further reading

Fielding, R. and Reschke, J. (2014) *Hypertext Transfer Protocol (HTTP/1.1): Conditional Requests*. RFC7232.

<https://tools.ietf.org/html/rfc7232>

Next Lecture: Cookies